



Product Summary

ANN-MB series

Multi-band, high precision GNSS antennas

Highlights

- Multi-band (L1, L2/E5b/B2I) active GNSS antennas with excellent price-performance ratio
- Supports GPS, GLONASS, Galileo, and BeiDou
- Fast and easy antenna solution for high precision applications
- Versatile mounting and connector options



60.0 x 82.0 x 22.5 mm

Product description

The u-blox ANN-MB multi-band (L1, L2/E5b/B2I) active GNSS antennas are designed to reduce time to market for the next generation of high precision GNSS applications, which require highly accurate location abilities. The compact design, excellent price-performance ratio, and versatile mounting and connector choices provide customers with fast, easy, and reliable multi-band antenna solutions. The ANN-MB antenna is a perfect match to the latest u-blox F9 platform including the ZED-F9P module, thus providing customers with the valuable antenna solution they need to minimize design-in efforts.

Patch antenna characteristics

	L1 Band	L2/E5b/B2I Band
Frequency	1559 - 1606 MHz	1197 - 1249 MHz
VSWR	Max. 2.0	Max. 2.0
Impedance	50 Ω	50 Ω
Peak gain (on \varnothing 15 cm ground plane)	Typ. 3.5 dBic	Typ. 0 - 2.0 dBic
Polarization	RHCP	RHCP

Amplifier characteristics

	L1 Band	L2/E5b/B2I Band
Frequency	1559 - 1606 MHz	1197 - 1249 MHz
Gain without cable (@ 5 V)	28 \pm 3.0 dB	28 \pm 3.0 dB
Noise figure (@ 5 V)	Max. 2.8 dB	Max. 3.2 dB
Output VSWR	Max. 2.0	Max. 2.0
DC voltage	3.0 - 5.0 V	
DC current (@ 5 V)	Typ. 15.0 mA	

Mechanical data

Weight	173 g (Typ. including cable)
Size	60.0 x 82.0 x 22.5 mm
Cable	5 m RG174 standard
Connectors (choice)	SMA, SMB, MCX
Mounting	Magnetic base, fixed installation option
Housing color	Black

Certifications and approvals

CE approval	Based on Radio Equipment Directive (RED) 2014/53/EU and the Restriction of the use of certain Hazardous Substances Directive (RoHS) 2011/65/EU and 2015/863/EU
-------------	--

Environmental data

Operating temperature	-40 °C to +85 °C
Storage temperature	-40 °C to +85 °C
Water proof	IP 67

Product variants

ANN-MB-00	Multi-band active GNSS antenna with 5 m cable and SMA connector
ANN-MB-01	Multi-band active GNSS antenna with 5 m cable and SMB connector
ANN-MB-02	Multi-band active GNSS antenna with 5 m cable and MCX connector

Legal Notice:

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com.
Copyright © 2019, u-blox AG

Further information

For contact information, see www.u-blox.com/contact-us.

For more product details and ordering information, see the product data sheet.